
ON

WLCSP36 2.43x2.43x0.488 CASE 567WJ ISSUE A


DATE 03 OCT 2018




NOTES:

- 1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 2009.
- 2. CONTROLLING DIMENSION: MILLIMETERS
- 3. DATUM C APPLIES TO THE SPHERICAL CROWN OF THE SOLDER BALLS

	MILLIMETERS			
DIM	MIN.	NOM.	MAX.	
Α	0.450	0.488	0.526	
A1	0.176	0.196	0.216	
A2	0.274	0.292	0.310	
b	0.240	0.260	0.280	
D	2.400	2.430	2.460	
E	2.400	2.430	2.460	
е	0.40 BSC			
х	0.200	0.215	0.230	
у	0.200	0.215	0.230	





(Ø0.215)Bottom of Cu Pad ⊕ ⊕ ○ ○ ○ ○ ○ ⊕ ○ ○ ○ ○ ○ ⊕ ○ ○ ○ ○
RECOMMENDED MOUNTING FOOTPRINT

(NSMD PAD TYPE)

DOCUMENT NUMBER:	98AON87484G	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.		
DESCRIPTION:	WLCSP36 2.43x2.43x0.488		PAGE 1 OF 1	

ON Semiconductor and are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. ON Semiconductor does not convey any license under its patent rights nor the rights of others.