






MSOP10, 3x3 CASE 846AE **ISSUE A**

DATE 20 JUN 2017





RECOMMENDED **SOLDERING FOOTPRINT***



DIMENSIONS: MILLIMETERS

*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

NOTES:

- DIMENSIONS AND TOLERANCING PER ASME Y14.5M, 1994.
 CONTROLLING DIMENSIONS: MILLIMETERS.
 DIMENSION 6 DOES NOT INCLUDE DAMBAR PROTRUSION.
 ALLOWABLE DAMBAR PROTRUSION SHALL BE 0.10 MM IN
- ALLOWABLE DAMBAR PROTRUSION SHALL BE 0.10 MM IN EXCESS OF MAXIMUM MATERIAL CONDITION.
 DIMENSION D DOES NOT INCLUDE MOLD FLASH,
 PROTRUSIONS, OR GATE BURRS. MOLD FLASH,
 PROTRUSIONS, OR GATE BURRS SHALL NOT EXCEED 0.15
 MM PER SIDE. DIMENSION E DOES NOT INCLUDE INTERLEAD FLASH OR PROTRUSION. INTERLEAD FLASH OR
 PROTRUSION SHALL NOT EXCEED 0.25 MM PER SIDE.
 DIMENSIONS DANDE ARE DETERMINED AT DATUME. DIMENSIONS D AND E ARE DETERMINED AT DATUM F. DATUMS A AND B TO BE DETERMINED AT DATUM F.
- A1 IS DEFINED AS THE VERTICAL DISTANCE FROM THE SEATING PLANE TO THE LOWEST POINT ON THE PACKAGE

	MILLIMETERS			
DIM	MIN	NOM	MAX	
Α			1.10	
A1	0.00	0.05	0.15	
A2	0.75	0.85	0.95	
b	0.17		0.27	
С	0.13		0.23	
D	2.90	3.00	3.10	
Е	4.75	4.90	5.05	
E1	2.90	3.00	3.10	
е	0.50 BSC			
L	0.40	0.70	0.80	
L1	0.95 REF			
L2	0.25 BSC			
θ	0°		8°	

GENERIC MARKING DIAGRAM*



XXXX = Specific Device Code = Assembly Location Α

Υ = Year W = Work Week = Pb-Free Package

(Note: Microdot may be in either location)

*This information is generic. Please refer to device data sheet for actual part marking. Pb-Free indicator, "G" or microdot " ■", may or may not be present and may be in either location. Some products may not follow the Generic Marking.

DOCUMENT NUMBER:	98AON34098E	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.		
DESCRIPTION:	MSOP10, 3X3		PAGE 1 OF 1	

onsemi and ONSEMI are trademarks of Semiconductor Components Industries, LLC dba onsemi or its subsidiaries in the United States and/or other countries. onsemi reserves the right to make changes without further notice to any products herein. onsemi makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.